

Valves & Couplers Fittings & Lids



 **NORWESCO**



Valves, Couplers, Fittings & Lids


Norwesco is your complete source for the high-performance products required for your fluid handling needs.

We take pride in our ability to respond quickly and effectively to your needs with same day order processing.

OUR CUSTOMER PROMISE TO YOU:

Dependable Service
High Quality Products
Affordable Prices

Call Norwesco at **800-328-3420** or visit **norwesco.com** for more information about our fluid handling products.



Meets Milspecs
Guidelines

Norwesco Cam Action Couplers are manufactured to standardized dimensions and tolerances and work with couplers from any manufacturer that chooses the gold standard: **MIL-C-27487**.



Table of Contents

p. 4-5 CAM ACTION COUPLERS & ADAPTERS

- Manufactured from glass-reinforced polypropylene
- Interchangeable with other couplers and adapters

p. 6-7 VALVES

Includes a wide variety of valves:

- Bolted Ball and Compact Ball Valves
- Single Union and Multi-Port Ball Valves
- Stainless Steel Ball Valves

p. 8-9 FLANGE BALL VALVES & FLANGE FITTINGS

- Provides quick and easy assembly
- No pipe tape or sealant necessary

p. 10-11 THREADED POLYPROPYLENE FITTINGS

Manufactured from glass-reinforced polypropylene for strength and durability and includes a wide variety of:

- Tees
- Crosses
- Elbows
- Nipples
- Hose Barbs

p. 12-13 BULKHEADS & BOLTED FITTINGS

- Comes standard with EPDM gaskets or Viton gaskets as an option
- Offered in a variety of sizes and thread configuration in either polypropylene or stainless steel

p. 14-15 STRAINERS & LIDS


- A variety of strainers & screens to keep liquids clean and moving
- Lids for every polypropylene tank



CAM ACTION COUPLERS & ADAPTERS

- Manufactured from glass reinforced polypropylene
- 304 stainless steel cam arms, pins, and clips with EPDM gaskets
- Built to **MIL-C-27487** size specifications and National Pipe Thread standards to ensure interchangeability with other brands of couplers
- 1/2" couplings interchange with all 3/4" couplings. Only the thread and hose barbs are 1/2". 1-1/4" and 1-1/2" couplings interchange in the same manner.

1/2 to 2"	100 psi	125 psi	70 psi
	0° F	70° F	150° F
3" to 4"	70 psi	90 psi	50 psi



Norwesco Cam Action Couplers are manufactured to the standardized dimensions and tolerances and work with couplers from any manufacturer that chooses the gold standard: **MIL-C-27487**.

'A' Male Adapter Female Thread

Size	Part No.
1/2"	61199
3/4"	61207
1"	61215
1 1/4"	61223
1 1/2"	61231
2"	61239
3"	61247
4"	62789



'B' Female Coupler Male Thread

Size	Part No.
1/2"	61255
3/4"	61259
1"	61263
1 1/4"	61267
1 1/2"	61271
2"	61275
2" (Long)	63961
3"	61279
3" (Long)	63962
4"	62790



'C' Female Coupler Hose Shank

Size	Part No.
1/2"	61256
3/4"	61260
1"	61264
1 1/4"	61268
1 1/2"	61272
2"	61276
3"	61280
3" (3 arms)	64136
4"	62791



'D' Female Coupler Female Thread

Size	Part No.
1/2"	61257
3/4"	61261
1"	61265
1 1/4"	61269
1 1/2"	61273
2"	61277
3"	61281
4"	62792



'E' Male Adapter Hose Shank

Size	Part No.
1/2"	61203
3/4"	61211
1"	61219
1 1/4"	61227
1 1/2"	61235
2"	61243
3"	61251
4"	62793



'F' Male Adapter Male Thread

Size	Part No.
1/2"	61204
3/4"	61212
1"	61220
1 1/4"	61228
1 1/2"	61236
2"	61244
3"	61252
4"	62794



90° 'A' Male Adapter Female Thread

Size	Part No.
1 1/2"	61293
2"	61296



90° 'C' Female Coupler Hose Shank

Size	Part No.
1 1/2"	61299
2"	61301



90° 'D' Female Coupler Female Thread

Size	Part No.
1 1/2"	61300
2"	61302



90° 'F' Male Adapter Male Thread

Size	Part No.
1 1/2"	61289
2"	61291



'DC' Dust Cap for Male Adapter

Size	Part No.
1/2"	61258
3/4"	61258
1"	61266
1 1/4"	61274
1 1/2"	61274
2"	61278
3"	61282
4"	62795



'DP' Dust Plug for Female Coupler

Size	Part No.
1/2"	61214
3/4"	61214
1"	61222
1 1/4"	61238
1 1/2"	61238
2"	61246
3"	61254
4"	62796



Specialty Couplings

Size	Part No.
3" male adapter x 2" male adapter	64133
3" male adapter x 3" male adapter	64134
3" female coupler x 2" male adapter	64135



4" female fittings (B, C, D, and DC)
all have 3 arms as per standard
MIL-C-27487




1-1/4", 1-1/2", and 2" Couplers
come with locking pins



BOLTED BALL, COMPACT BOLTED, NOZZLE VALVES

- Manufactured from glass-reinforced polypropylene for strength and durability — will never rust or corrode
- Self-aligning ball rotates freely against Teflon seats
- Unique body-to-flange design allows for low torque on/off operation
- Viton O-ring stem seal and EPDM O-ring body seal
- Available with blue Norwesco handle or blank yellow handle
- All valves tested by air pressure under water



Full Port Bolted FPT x FPT

Size	Bolts	Part No.
1/2"	4	60540
3/4"	4	60541
1"	4	60543
1 1/4"	4	60527
1 1/2"	4	60526
2"	6	60528
3"	6	61720
4"	6	62787



Bolted MPT x FPT (Ideal for tanks)

Size	Bolts	Part No.
2" standard	4	62046
2" full	6	61876
3" full	6	62047



Standard Port Bolted FPT x FPT

Size	Bolts	Part No.
1"	4	60542
1 1/4"	4	61734
2"	4	60529



Nozzle Valves (Bolted Ball and Single Union)

Size	Bolts/Union	Part No.
1" 45°	single union	60479
1 1/2" full	6	60544
2" std	6	60545
2" full	6	60546



2" Full Port Compact

Connections	Bolts	Part No.
MPT X FPT	4	62286
FPT X FPT	4	62287
FPT X Male Adapter	4	62314
MPT X Male Adapter	4	62288



Single Union Full Port

- Manufactured from polypropylene
- Teflon seats
- EPDM O-rings (Viton kits available)
- All valves tested by air pressure under water



Size	Part No.
1/2"	60409
3/4"	60410
1"	60411
1 1/4"	60412
1 1/2"	60413
2"	60414
3"	60415

Multi-Port Ball



Size	Part No.
2" Bolted side-load	64258
2" Bolted bottom-load	64139
3/4" True Union (Full port)	60417
2" Multi Port (Std port)	60418

Stainless Steel Full Port

- Manufactured from 316 stainless steel
- Full port construction
- Water, oil and gas rated to 1000 PSI
- Lockable handle
- Teflon seats and seals
- Polished stainless steel ball for precise operation
- Tested by air pressure under water




Size	Part No.
1/2"	60481
3/4"	60482
1"	60483
1 1/2"	60485
2"	60487
3"	60488



FLANGE BALL VALVES & FITTINGS

- Quick and easy assembly – No thread tape or sealant necessary
- Positive seals
- Easy on/off hose connection
- 360° orientation
- Valves and fittings are manufactured from glass-reinforced polypropylene for strength and durability — will never rust or corrode

All Norwesco flange fittings are full port and mate with other manufacturers 1" = 100, 1 1/2" = 200, 2" = 220, 3" = 300



Flange Clamps Stainless Steel

Size	Part No.
1"	62932
2"	62933
3"	62934

Flange Gasket EPDM

Size	Part No.
1"	62935
2"	61574
3"	61575



Flange Ball Valves

- Self-aligning ball rotates freely against Teflon seats
- Unique body-to-flange design allows for low torque on/off operation
- Viton O-ring stem seal and EPDM O-ring body seal
- Available with blue Norwesco handle or blank yellow handle
- Pressure rated at 125 PSI @ 70 degrees F
- All valves tested by air pressure under water

Flange 3-Way

Size	Type	Part No.
2"	Side Load	64138
3"	Bottom Load	64140



Flange Full Port

Size	Bolts	Part No.
1"	4	63027
1 1/2"	4	64256
2"	4	63122
3"	6	63124



Flange Tee

Size	Part No.
1"	62912
2"	63100
3"	63111



Flange Elbow

Size	Part No.
1"	62913
2"	63101
2" 45°	64483
3"	63112



Flange Coupling

Size	Part No.
1"	62914
2"	63102
3"	63113



Flange x MPT

Size	Part No.
1" Flange x 3/4" MPT	63098
1" Flange x 1" MPT	62915
1" Flange x 1 1/4" MPT	63099
2" Flange x 2" MPT	63103
3" Flange x 3" MPT	63114



Flange x FPT

Size	Part No.
1" Flange x 1" FPT	62916
2" Flange x 2" FPT	63104



Flange x HB

Size	Part No.
1" Flange x 3/4" HB	62917
1" Flange x 1" HB	62918
1" Flange x 1 1/4" HB	62919
2" Flange x 1 1/2" HB	63105
2" Flange x 2" HB	63106
3" Flange x 2" HB	63115
3" Flange x 3" HB	63116



Flange x HB 90°

Size	Part No.
1" Flange x 3/4" HB 90°	62920
1" Flange x 1" HB 90°	62921
1" Flange x 1 1/4" HB 90°	62922
2" Flange x 1 1/2" HB 90°	63107
2" Flange x 2" HB 90°	63108
3" Flange x 2" HB 90°	63117
2" Flange x 3" HB 90°	63118



Flange Cross

Size	Part No.
1"	62923
2"	63109
3"	63119



Flange Plug

Size	Part No.
1"	62924
1" w 1/4" FPT	62925
2"	63110
3"	63120



Flange Reducing Coupling

Size	Part No.
2" Flange x 1" Flange	62927
2" Flange x 1 1/2" Flange	64250
3" Flange x 1" Flange	64893
3" Flange x 2" Flange	62928



Flange x Male Coupler

Size	Part No.
2" Flange x 2" Male Coupler	62926
3" Flange x 3" Male Coupler	63121
2" Flange x 2" HB	64405
3" Flange x 3" HB	64404



Flange Sweep 90's

Size	Part No.
2" Flange x 2" Flange	64484
2" Flange x 2" MPT	64406
2" Flange x 2" Hose Barb	64405
2" Flange x 2" Male Adapter	64137
3" Flange x 3" Hose Barb	64404
3" Flange x 3" MPT	64403



THREADED POLYPROPYLENE FITTINGS

- Manufactured from glass-reinforced polypropylene for strength and durability
- Schedule 80 design
- National pipe thread

3/8" to 4" 0° F 70° F 250° F
120 psi 150 psi 90 psi

Tees

Size	Part No.
3/8"	62464
1/2"	62209
3/4"	62210
1"	62211
1 1/4"	62212
1 1/2"	62213
2"	62190
3"	62214



Elbows

Size	Part No.
3/8"	62465
1/2"	62215
3/4"	62216
1"	62217
1 1/4"	62218
1 1/2"	62219
2"	62191
3"	62220



90° Street Elbows

Size	Part No.
3/8"	62460
1/2"	62243
3/4"	62244
1"	62245
1 1/4"	62246
1 1/2"	62247
2"	62199
3"	62248



45° Street Elbows

Size	Part No.
3/4"	62907
1"	62908
1/4"	62909
1 1/2"	62910
2"	62911



Crosses

Size	Part No.
3/4"	62262
1"	62263
1 1/4"	62264
1 1/2"	62265
2"	62202



King Nipples

Size	Part No.
1/2"	61303
3/4"	61304
1"	61305
1 x 1" 90°	64153
1 1/4" x 1" 90°	62469
1 1/2"	61319
2"	61861
3"	61321
4"	62468

0° F 70° F 150° F
100 psi 125 psi 70 psi



Straight Nipples

Size	Part No.	Size	Part No.
3/8" x short	62459	1 1/4" x 6"	62228
1/2" x short	62221	1 1/2" x short	60547
1/2" x 3"	62222	1 1/2" x 4"	62229
3/4" x short	60554	1 1/2" x 6"	62230
3/4" x 4"	62223	2" x short	60548
3/4" x 6"	62224	2" x 4"	62192
1" x short	60555	2" x 6"	62193
1" x 4"	62225	3" x short	61769
1" x 6"	62226	3" x 6"	62232
1 1/4" x short	60556	4" x short	62467
1 1/4" x 4"	62227		



Reducer Nipples

Size	Part No.
1/2" x 3/8"	62455
3/4" x 1/2"	62233
1" x 1/2"	62456
1" x 3/4"	62234
1 1/4" x 3/4"	62457
1 1/4" x 1"	62235
1 1/2" x 1"	62458
1 1/2" x 1 1/4"	62236
2" x 1 1/2"	60549
3" x 2"	61768
4" x 3"	62938



Reducer Bushings

Size	Part No.
3/8" x 1/4"	62466
1/2" x 1/4"	62267
1/2" x 3/8"	62268
3/4" x 1/8"	62269
3/4" x 1/4"	62270
3/4" x 3/8"	62271
3/4" x 1/2"	62272
1" x 1/8"	62273
1" x 1/4"	62274
1" x 1/2"	62275
1" x 3/4"	62276
1 1/4" x 3/4"	62277
1 1/4" x 1"	62278
1 1/2" x 3/4"	62279



Size	Part No.
1 1/2" x 1"	62280
1 1/2" x 1 1/4"	62281
2" x 3/4"	62195
2" x 1"	62196
2" x 1 1/4"	62197
2" x 1 1/2"	62198
3" x 1 1/2"	62282
3" x 2"	60330

Caps

Size	Part No.
1/2"	62462
3/4"	62250
1"	62251
1 1/4"	62463
1 1/5"	62253
2"	62200
3"	62254



Plugs

Size	Part No.
1/2"	62255
3/4"	62256
1"	62257
1 1/4"	62258
1 1/5"	62259
2"	62201
3"	62260



Couplings

Size	Part No.
3/8"	62461
1/2"	62237
3/4"	62238
1"	62239
1 1/4"	62240
1 1/5"	62241
2"	62194
3"	62242



BULKHEADS & BOLTED FITTINGS

Polypropylene Bulkheads

- Supplied with EPDM gaskets – optional Viton available
- See www.norwesco.com for a full listing of specifications, gasket and siphon tube options, and torque charts

Polypropylene Bulkheads Double Threaded

- Bulkheads marked Std (standard duty) are for thinner tank walls
- Bulkheads marked HD (heavy duty) are for thicker tank walls

Size	Hole Size	Part No.
1/2"	1 7/16"	62834
3/4"	1 7/16"	60401
3/4" HD	1 5/8"	62798
1 "	2 1/4"	60427
1 1/4"	2 1/4"	60403
1 1/2" STD	2 3/8"	63931
1 1/2"	3"	60124
2"	3"	60405
2" STD	3"	63481
2" HD	3 1/4"	63683
3"	4 1/2"	62299
4"	5 3/4"	62171



Self-Aligning Bulkhead

- For installations in tank domes where a vertical connection is required
- Only to be installed above liquid level

Size	Hole Size	Part No.
2"	4 1/2"	63668



MPT Vent Caps & Anti-Vortex

Size	Part No.
2" screened vent	63266
2" screenless vent/anti-vortex	63316
2" anti-vortex only	62399
3" screened vent	63845



Anti-Vortex Bulkhead

Size	Hole Size	Part No.
1 1/4"	2 1/4"	63065



Polypropylene Bolted Double Threaded

- 316 stainless steel bolts
- EPDM gaskets (2) standard – optional Viton available
- 2" / 3" fittings available with encapsulated interior bolts

Size	Part No.
3/4"	60502
1 "	60505
1 1/2"	60513
2"	60516
2" Encapsulated	64216
3"	62471
3" Encapsulated	64217



Polypropylene Total-Drain

- For complete drainage in floor/sump installations
- 316 stainless steel bolts / EPDM gaskets

Size	Bolts	Part No.
2"	4	62470
3"	6	62472



Stainless Steel Full Coupling Bolted

- 316 s/s and EPDM gasket
- Optional gaskets in Viton or X-Linked polyethylene
- Double threaded coupler passes through tank wall

Size	Bolts	Part No.
3/4"	4	64251
1"	4	64252
1 1/2"	4	64253
2"	4	64202
3"	6	64195
4"	8	64254



Stainless Steel Bolted

- 316 s/s and EPDM gaskets standard
- Optional Viton gaskets available
- Designed for installation in thick tank walls

Size	Bolts	Part No.
1"	4	63972
1 1/2"	4	63973
2"	4	63974
3"	6	64194



Y-LINE AND T-LINE STRAINERS

- Manufactured from polypropylene. Y-Line series is glass-reinforced
- Standard with EPDM gaskets
- Easy access to the straining element for cleaning
- 1/2" to 2" Y-Line strainers feature overmolded screens colored according to ISO/FDIS-19372
- 3" Y-Line screens are stainless steel with a polypropylene reinforcing frame
- 12 to 100 mesh screens constructed from 304 stainless steel

Y-Line Strainer

1/2" to 2"	70 psi	90 psi	50 psi
	0° F	70° F	150° F
3"	55 psi	70 psi	40 psi

T-Line Strainer

1/2" to 1"	80 psi	100 psi	56 psi
	0° F	70° F	150° F

Y-Line Strainers

Size	Part No.	Size	Part No.	Size	Part No.	Size	Part No.
1/2" 20 mesh	64169	1" 50 mesh	64295	2" 20 mesh	64275	3" 12 mesh	62338
1/2" 50 mesh	64170	1" 100 mesh	64296	2" 50 mesh	64276	3" 20 mesh	62339
1/2" 80 mesh	64171	1 1/4" 20 mesh	64297	2" 100 mesh	64277	3" 40 mesh	62340
1/2" 100 mesh	64172	1 1/4" 50 mesh	64298				
3/4" 20 mesh	64173	1 1/4" 100 mesh	64299				
3/4" 50 mesh	64174						
3/4" 80 mesh	64175	1 1/2" 20 mesh	64272				
3/4" 100 mesh	64176	1 1/2" 50 mesh	64273				
1" 20 mesh	64294	1 1/2" 100 mesh	64274				



Y-Line Strainer Screens (1/2" to 2")

Size	Part No.	Size	Part No.	Size	Part No.
20 mesh 1/2", 3/4"	64177	20 mesh 1", 1 1/4"	64300	20 mesh 1 1/2", 2"	64260
50 mesh 1/2", 3/4"	64178	50 mesh 1", 1 1/4"	64292	50 mesh 1 1/2", 2"	64261
80 mesh 1/2", 3/4"	64179	100 mesh 1", 1 1/4"	64293	100 mesh 1 1/2", 2"	64262
100 mesh 1/2", 3/4"	64180				

Y-Line Strainer Screens (3")

Size	Part No.
12 mesh 3"	62249
20 mesh 3"	62252
40 mesh 3"	62261
80 mesh 3"	62400

20 Mesh



50 Mesh



80 Mesh



100 Mesh



T-Line Strainers

Size	Part No.
1/2" 20 mesh	64281
1/2" 40 mesh	64282
1/2" 80 mesh	64283
3/4" 20 mesh	64284
3/4" 40 mesh	64285
3/4" 80 mesh	64286
1" 20 mesh	64287
1" 40 mesh	64288
1" 80 mesh	64289



T-Line Replacement Screens

Size	Part No.
20 mesh	61404
40 mesh	61405
80 mesh	61406



See www.norwesco.com for complete details on spare parts, operating pressures, and standard packaging.

TANK LIDS

- All thread-in lids are manufactured from high density polyethylene
- Hinged lids are manufactured from a unique co-polymer for additional strength and durability
- Norwesco recommends replacing lost or broken lids with a complete ring and lid assembly
- All 22", 16" and 8" lids are available in vented and non-vented versions
- Hinged lids have a locking tab which can be secured with any standard padlock

5" Lids

Description	Part No.
*Vented lid ball check and gasket	63484
Vented lid 2" FPT center	63264
Ventless hinged lid	63673



8" Lids

Description	Part No.
Vented lid & ring assembly	60032
*Vented lid for molded-in threads	63480



16" Lids

Description	Part No.
Vented lid & ring 4" removable center	60038
*Vented lid & ring blue snap in vent	63485
Vented lid & ring 3" FPT center	63868
Ventless lid & ring	60367



16" Strainer Basket

Description	Part No.
For use with 16" threaded lids	67374



18" & 24" Lids

Description	Part No.
24" vented lid & ring assembly	64443
*18" vented lid & ring assembly	64448



22" Lids

Description	Part No.
*Vented lid & ring assembly	63679
Ventless lid & ring assembly	63863



Hinged Lid Assemblies

Description	Part No.
*16" Vented	62532
16" Ventless	63390
22" Vented	63874
22" Ventless	64190



* Photo is shown



Westfall Company, Inc.
124 Workman Court
Eureka, MO 63025
636-938-3113
sales@westfallcompany.com
www.westfalltanks.com



Call Norwesco for your fluid handling needs.



Norwesco is your complete source for the high-performance valves, couplers, fittings, and lids required in agricultural and industrial fluid handling applications.

Norwesco valves, couplers, fittings, and lids are used by these premium brands and manufacturers.

